

immhydraulics

Hydraulics (UK) Ltd

**Your One Stop Supplier
for all of your
Requirements.**

Supplying Quality Hydraulic products direct from the manufacturer.

Thermoplastic Sewer Hose

For your Sewer flushing requirements, make sure you purchase a superior hose that you can continually rely on!!!!

We can supply either loose hose or bespoke hose assemblies, both at very competitive prices.

Call or email our sales team who will assist you with your requirements.



Technical Data.

Internal core construction = Thermoplastic compound.

Reinforcement with two braids of polyester fibre.

Exterior covering in Anti-abrasive perforated polyurethane.

Available from 1/2" to 1.1/4" up to 250 Meter Lengths.

Temp range = -40 to +55 Centigrade.

Safety Factor = 2.5 x 1

Part Number	Inch	Internal	External	Min. Burst	Min. Working	Min. Bend	Weight
TF-1PS-08	1/2"	13.0mm	22.4mm	700 Bar	280 Bar	75 mm	295 g/m
TF-1PS-10	5/8"	16.0mm	26.5mm	550 Bar	220 Bar	100 mm	402 g/m
TF-1PS-12	3/4"	19.2mm	29.5mm	500 Bar	200 Bar	120 mm	454 g/m
TF-1PS-16	1"	25.6mm	36.8mm	500 Bar	200 Bar	150 mm	635 g/m
TF-1PS-20	1.1/4"	32.0mm	45.5mm	500 Bar	200 Bar	235 mm	915 g/m



Units 1 & 2, Block 3, Shenstone Trading Estate,

Halesowen, West Midlands. B63 3XB

Phone: +44 (0)121 550 1115 Fax: +44 (0)121 585 7920

Email: sales@immhydraulics.co.uk

Web : www.immhydraulics.co.uk

